





T. +371 67 607 900 F. +371 67 607 901 latvia@kiwa.com

www.kiwa.com/lv



Certificate of constancy of performance No. 1325-CPR-3363A

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product(s)

Wood wool (WW) thermal insulation products:
boards CEWOOD CW-W, CEWOOD CW-G, CEWOOD CW-A2,
CEWOOD CW-BARCODE and composite board CEWOOD CW-PLUS
according to the Annex,

PLACED ON THE MARKET UNDER THE NAME OF:

SIA "CEWOOD"

Galdusalas-1, Jaunlaicene, Alūksne, LV - 4336, Latvia; reg. No. 45403042702

AND PRODUCED IN THE MANUFACTURING PLANT(S): SIA "CEWOOD" "Galdusalas-1", Jaunlaicenes pagasts, Alūksnes novads, LV - 4336, Latvia

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 13168:2012+A1:2015

Under system 1 for the performance set out in this certificate are applied and that the performance of the construction product is assessed to remain constant.

This certificate was first issued on 8 September 2016 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by notified factory production control certification body.



dertificate issued on 1 (one) page with Annex on 1 (one) page



Product: Wood wool (WW) thermal insulation products; boards CEWOOD CW-W, CEWOOD CW-G, CEWOOD CW-A2, CEWOOD CW-BARCODE and composite board CEWOOD CW-PLUS **Manufacturer:** SIA "CEWOOD" "Galdusalas-1", Jaunlaicenes pagasts, Alūksnes novads, LV-4336, Latvia

CEWOOD	CW-W
Shavings of wood	0,7 - 1,0 - 1,5 mm
Binder	cement
Thickness of board	15 - 50 mm
Density of board	370 - 550 kg/m ³
Reaction to Fire	B-s1,d0
CEWOOL	CW-G
Shavings of wood	3,0 mm
Binder	cement
Thickness of board	25 - 100 mm
Density of board	324 - 506 kg/m ³
Reaction to Fire	B-s1,d0
CEWOOD	
Shavings of wood	1 - 1,5 mm
Binder	cement
Thickness of board	15 mm / 25 mm
Density of board	830 kg/m ³ / 580 kg/m ³
Reaction to Fire	A2-s1,d0
CEWOOD CW	
Shavings of wood	1 mm
Binder	cement
Thickness of board	25 mm
Density of board	477 - 583 kg/m ³
Reaction to Fire	B-s1,d0
Composite board Cl	
Overall thickness of board	45 -125 mm
Overall density of board	370 - 550 kg/m ³
Reaction to Fire	B-s1,d0
WW b	
Shavings of wood	1 - 1,5 mm
Binder	cement
Density of board	420 kg/m ³
Thickness of board	25 mm
MW bo	pard
Density of board	125 - 255 kg/m ³
Thickness of board	20 -100 mm
Thickness of board	s institucija

Mārtiņš Maskays

Certification Manager

EN ISO/IEC 17065 S1-182

T. +371 67 607 900 F. +371 67 607 901 latvia@kiwa.com

AS Inspecta Latvia Skanstes iela 54A, Rīga LV-1013, Latvija